

# FIXED TEMPERATURE SWITCHES TYPE TRM.204

Max voltage 230 Vca  
 Contact Normally Open or Closed  
 Current 10 A  
 Differential  $10\text{ }^{\circ}\text{C} \pm 4\text{ }^{\circ}\text{C}$   
 Accuracy  $\pm 3\text{ }^{\circ}\text{C}$   
 Max temperature  $+50\text{ }^{\circ}\text{C}$  over spv  
 Max pressure 100 bar  
 Protection IP 65 with DIN Connector



Rev.01/2015

## ORDERING CODE

**TRM.204 070 15GO 2 S1**

<b>TYPE</b>	TRM.204
<b>RANGE</b>	040-050-060-070-080 090-100-110-120-130
<b>CONNECTION</b>	15 - 22K - 20
<b>THREAD</b>	G - C - N
<b>MATERIAL</b>	O - S
<b>CONTACT</b>	1 - 2
<b>CONNECTOR</b>	S1 - S3

## CODE EXPLANATION

**TIPO**  
 TRM.204 Termostato bimetallico fisso

**RANGE**

040	40 °C
050	50 °C
060	60 °C
070	70 °C
080	80 °C
090	90 °C
100	100 °C
110	110 °C
120	120 °C
130	130 °C

**ATTACCHI**

15	1/2"
22K	M22x1,5 (su richiesta)
20	3/4" (su richiesta)

**FILETTATURE**

G	UNI 228/1
C	UNI 7/1 (su richiesta)
N	NPT (su richiesta)

**MATERIALI**

O	Ottone
S	Acc. Inox (su richiesta)

**CONTATTI ELETTRICI (a riposo)**

1	Normalment Aperto
2	Normalmente Chiuso

**USCITA ELETTRICA**

S1	DIN 43650A
S3	DIN 43650A Girevole

