

Technical data/accessories

Smart Probes – refrigeration set

testo Smart Probes refrigeration set for servicing, commissioning and error detection on air conditioning and refrigeration systems. Consists of: 2x testo 115i, 2x testo 549i, testo Smart Case (refrigeration), batteries, calibration protocol



Order no. 0563 0002

EUR 220.00



testo Smart Probes App

The App turns your smartphone/tablet into the display of up to 6 Testo Smart Probes at the same time. The operation of the measuring instruments as well as the display of the measurement values take place by Bluetooth via the Testo Smart Probes App on your smartphone or tablet – independently of the measurement location. In addition to this, you can use the App to create measurement reports, add photos and comments to these, and send them by e-mail. For iOS and Android.

1981 1824/msp//10.2015

	testo 115i	testo 549i
Sensor type	NTC	Pressure
Measuring range	-40 to +150 °C	-1 to 60 bar
Accuracy ±1 digit	±1.3 °C (-20 to +85 °C)	0.5 % of final value
Resolution	0.1 °C	0.01 bar
Connection		7/16" – UNF
Overload rel.		65 bar
Compatibility	requires iOS 8.3 or newer / Android 4.3 or newer requires mobile end device with Bluetooth 4.0	
Storage temperature	-20 to +60 °C	
Operating temperature	-20 to +50 °C	
Battery type	3 micro batteries AAA	
Battery life	250 hrs	150 hrs
Dimensions	183 x 90 x 30 mm	125 x 32 x 31 mm
Measurable media		CFC, HFC, HCFC, N, H ₂ O, CO ₂
Warranty	2 years	

Subject to change, including technical modifications, without notice.
All prices net plus shipping costs and VAT valid from 01/11/2015.
Payment with in 30 days net.

Accessories

	Order no.	EUR
ISO calibration certificate relative pressure, 3 measurement points distributed over the entire measuring range	0520 0085	69.00
ISO calibration certificate temperature, one-point calibration for clamp thermometer, calibration point +60 °C	0520 0072	70.50

5???

0?PNSU00?

FDUNWHFD00