

BI-METALLIC TEMPERATURE SWITCHES TYPE T24

Max voltage:	250 Vac
Current:	2 A @ 250 Vac 3 A @ 24 Vdc
Working temperature:	-30 ÷ 145 °C
Switching temperature:	30 ÷ 120 in step of 5 °C
Tolerance:	± 3,5 °C
Isteresis:	< 5 °C
Certification:	CE
Contacts:	Normally Open (O) Normally Closed (C)
Material:	Brass
Electrical Protection:	IP00 IP54 with CP54 Protection Cap
Mounting:	Sw 24



Rev.02/2016

ORDERING CODE

T24 90 C 12

TYPE
Temperature switches Sw 24
TEMPERATURE AVAILABLE
30 - 35 - 40 - 45 - 50 - 55 - 60 65 - 70 - 75 - 80 - 85 - 90 - 95 100 - 105 - 110 - 115 - 120
CONTACT
O (open) - C (closed)
CONNECTION
14 - 38 - 12 - M14 - M22 M18 - M16 - U58

CODE EXPLANATION

TYPE	T24	Bi-Metallic Temperature Switches Sw 24
RANGE	30	30 °C ± 3,5°C
	35	35 °C ± 3,5°C
	40	40 °C ± 3,5°C
	45	45 °C ± 3,5°C
	50	50 °C ± 3,5°C
	55	55 °C ± 3,5°C
	60	60 °C ± 3,5°C
	65	65 °C ± 3,5°C
	70	70 °C ± 3,5°C
	75	75 °C ± 3,5°C
	80	80 °C ± 3,5°C
	85	85 °C ± 3,5°C
	90	90 °C ± 3,5°C
	95	95 °C ± 3,5°C
	100	100 °C ± 3,5°C
	105	105 °C ± 3,5°C
	110	110 °C ± 3,5°C
	115	115 °C ± 3,5°C
	120	120 °C ± 3,5°C

CONTACT

O	Normally Open
C	Normally Closed

CONNECTION Quote A

14	G14"
38	3/8" BSPP - L1=13,5 mm
12	1/2" BSPP - L1=13,5 mm
M14	M14 x 1,5 - L1=13,5 mm
M22	M22 x 1,5 - L1=13,5 mm
M18	M18 x 1,5 - L1=13,5 mm
M16	M16 x 1,5 - L1=13,5 mm
U58	5/8" UNF - L1=13,5 mm

SPECIAL EXECUTION

Special temperature range on request

